

selt
sun
protection
systems

**Fabrics
Slat Colours
Construction Colours**



TABLE OF CONTENTS

AWNING FABRICS.....	5
SOLID ACRYLIC FABRICS.....	8
WATERPROOF ACRYLIC FABRICS.....	15
ORCHESTRA ACRYLIC FABRICS.....	16
URBAN ACRYLIC FABRICS.....	17
LANDSCAPE MINI ACRYLIC FABRICS	18
LANDSCAPE ACRYLIC FABRICS	18
CLASSICAL ACRYLIC FABRICS.....	20
FANTASY ACRYLIC FABRICS	21
SCREEN FABRICS	27
SERGE 600.....	30
SERGE 1%.....	32
SERGE 600 BO LUNAR.....	33
POLYSCREEN® 550.....	34
POLYSCREEN® 550 GOLD & SILVER	35
POLYSCREEN® 350.....	36
POLYSCREEN® LUMINOUS.....	37
POLYSCREEN® 550 COUPAGE	38
POLYSCREEN® 314 BLACK OUT	39
SUNWORKER.....	40
SOLTIS® 92.....	41
SOLTIS® 99.....	42
VEROGLIM ACOUSTIC	43
PERGOLA SOLID FABRICS	44
SELT COLOURS.....	46
SLAT COLOURS.....	48
CONSTRUCTION COLOURS	50



AWNING FABRICS



Above pictograms apply to acrylic fabrics.

ACRYLIC FABRICS

WATERPROOF FABRICS

Technical data shown below are average values of the current production Die angegebenen technischen Daten sind Durchschnittswerte der laufenden Produktion Les données techniques ci-dessous sont des valeurs moyennes de la production courante	ACRYLIC	
Fabric Gewebe Tissu		Acrylic 100%, solution dyed Acryl 100%, spinndüsengefärbt Acrylique, 100% teint masse
Finishing Ausrüstung Traitement		Teflon - Cleangard
Weight Gewicht Poids total	DIN EN 12127	~ 300 g/m ²
Width Warenbreite Laize		120 cm
Colour fastness Farbechtheit Solidité des coloris	DIN EN ISO 105-B02	7-8 / 8
Oil repellency Ölabweisung Oléofugation	EN ISO 14419	4-5
Water repellency Wasserabweisung Résistance au mouillage superficiel	EN ISO 4920	100
Water column Wassersäule Colonne d'eau	EN 20 811	~ 330 mm
Tensile strength (daN/5 cm) Höchstzugkraft (daN/5 cm) Résistance à la rupture (daN/5 cm)	DIN EN ISO 13934-1	~ 140 / 95
Tear resistance (daN) Weft/Warp Weiterreißkraft (daN) Schuss/Kette Résistance à la déchirure (daN) Trame/Chaîne	EN ISO 13937-2	2.3 / 4

Acrylic fabrics guarantee the highest quality of the product, providing thermal comfort and protection against UV radiation. Made 100% out of acrylic fibre, dyed in chemical solution, provide excellent protection against colour loss. UV resistance coefficient is 7-8 at 8° scale. Impregnation with use of TEFLON® or SCOTCHGARD™ agents provides an excellent protective barrier and strengthens water-repellent qualities of the fabric, also preventing dirt adhering. Resistance to leaking: 330 mm water column. The advantage of acrylic fabric is also high resistance to tensile and tear.

Technical data shown below are average values of the current production Die angegebenen technischen Daten sind Durchschnittswerte der laufenden Produktion Les données techniques ci-dessous sont des valeurs moyennes de la production courante	ACRYLIC WATERPROOF	
Fabric Gewebe Tissu		Acrylic 100%, solution dyed Acryl 100%, spinndüsengefärbt Acrylique 100% teint masse
Finishing Ausrüstung Traitement		Teflon - Cleangard
Weight Gewicht Poids total	DIN EN 12127	~ 330 g/m ²
Width Warenbreite Laize		120 cm
Colour fastness Farbechtheit Solidité des coloris	DIN EN ISO 105-B02	7-8 / 8
Oil repellency Ölabweisung Oléofugation	EN ISO 14419	4-5
Water repellency Wasserabweisung Résistance au mouillage superficiel	EN ISO 4920	100
Water column Wassersäule Colonne d'eau	EN 20 811	~ 1000 mm
Tensile strength (daN/5 cm) Höchstzugkraft (daN/5 cm) Résistance à la rupture (daN/5 cm)	DIN EN ISO 13934-1	~ 140 / 95
Tear resistance (daN) Weft/Warp Weiterreißkraft (daN) Schuss/Kette Résistance à la déchirure (daN) Trame/Chaîne	EN ISO 13937-2	3 / 4

Waterproof acrylic fabrics are characterized by increased resistance to leaking - about 1000 mm water column. Weave structure together with modern impregnation technology provides high air permeability even on hot days. Oeko-Tex® guarantees that offered acrylic fabrics, subjected to special impregnation for water resistance, are not toxic.

SOLID

ACRYLIC FABRICS

BLANCO




2042 UV: 97% ГТот: 18%

TANDEM BLANCO




8442 UV: 40% ГТот: 18%

NATURAL




2929 UV: 97% ГТот: 18%

MARFIL



2143 UV: 97% ГТот: 16%

SIROCO




2226 UV: 98% ГТот: 12%

VANILLA




2687 UV: 97% ГТот: 17%

AMBER BEIGE




0814 UV: 99% ГТот: 15.66%

BEIGE




2038 UV: 99% ГТот: 11%

INTEGRAL




2838 UV: 99% ГТот: 8%

BERNA



2041 UV: 97% ГТот: 16%

MULTICO FLAME




7131 UV: 90% ГТот: 17%

NUAGES FLAME




6319 UV: 90% ГТот: 16%

AVENA




2296 UV: 98% ГТот: 11%

LIN MELANGE




8904 UV: 95% ГТот: 11%

TWEED BROWN




0403 UV: 99% ГТот: 6.82%

MINERAL




2831 UV: 99% ГТот: 7%

VISION




2250 UV: 99% ГТот: 7%

CHAUME PIGUE




U235 UV: 100% ГТот: 9%

CAFE



2316 UV: 99% ГТот: 5%

MARBLE




0923 UV: 99% Gtot: 12.8%

TWEED LATTE



7926 UV: 98% Gtot: 15%

SNOWFLAKE




3463 UV: 95% Gtot: 22%

TWEED ARGENT




0794 UV: 98% Gtot: 19%

DARK LINEN




6727 UV: 98% Gtot: 18%

SILVER WHITE




0364 UV: 99% Gtot: 7.67%

SILVER MELANGE



0028 UV: 99% Gtot: 7.36%

TANDEM PIEDRA



8445 UV: 80% Gtot: 7%

IRON



0937 UV: 99% Gtot: 6.57%

TWEED ROCK



7151 UV: 98% Gtot: 11%

SILVER




2821 UV: 97% Gtot: 13%

SILVER GREY




U190 UV: 90% Gtot: 15%

ZIP GREY



1597 UV: 98% Gtot: 13%

ZINC




2802 UV: 99% Gtot: 11%

PIERTA BEIGE




9415 UV: 98% Gtot: 8%

PERLA




2979 UV: 97% Gtot: 8%

ASH




0638 UV: 99% Gtot: 5.05%

ANTRACITA




8488 UV: 99% Gtot: 6%

TANDEM GRAFITO




8446 UV: 80% Gtot: 6%

EBONY TWEED



7324 UV: 98% Gtot: 10%

NEGRO



2170 UV: 99% Gtot: 5%

GRAPHITE ZIP




1524 UV: 98% Gtot: 12%

BASALT



8203 UV: 100% Gtot: 5%

FLANELLE



U104 UV: 100% Gtot: 5%

CHARCOAL TWEED



0402 UV: 99% Gtot: 5%

STITCH ANDESITE



0512 UV: 98% Gtot: 8%

STITCH CALCITE



0505 UV: 98% Gtot: 9%

STITCH RUBY



0507 UV: 98% Gtot: 9%

WHITE LINEN




8615 UV: 95% Gtot: 18%

PLATINUM



0715 UV: 90% Gtot: 12%

BREEZE




2777 UV: 99% Gtot: 6%

MARINE




2145 UV: 99% Gtot: 5%

AZUL




2018 UV: 99% Gtot: 7%

ORANGE




2050 UV: 99% Gtot: 13%

BRIGHT RED




2211 UV: 99% Gtot: 10%

PIMENT FIGUE




U412 UV: 100% Gtot: 10%

RIOJA




2210 UV: 99% Gtot: 8%

CARMIN FIGUE




U411 UV: 100% Gtot: 10%

GRANATE




2101 UV: 99% Gtot: 6%

SWITCH ROGUE



U390 UV: 100% Gtot: 8%

MARSEILLE FLAME




8854 UV: 100% Gtot: 11%

AMARILLO




2013 UV: 99% Gtot: 15%

TWEED SENAPE




0034 UV: 99% Gtot: 6.3%

CURRY




U105 UV: 100% Gtot: 12%

OCRE




2180 UV: 99% Gtot: 13%

POTIRON PIGUE




U413 UV: 100% Gtot: 10%

JADE




0396 UV: 99% Gtot: 8.12%

MELEZE PIGUE




U417 UV: 100% Gtot: 8%

VERDE BOTELLA



2245 UV: 99% Gtot: 6%

SWITCH EMPIRE



U393 UV: 100% Gtot: 8%

WATERPROOF


ACRYLIC FABRICS

BLANCO




8268 UV: 97% Gtot: 18%

MARFIL



8272 UV: 97% Gtot: 16%

AMARILLO




8265 UV: 99% Gtot: 15%

COCO



2047 UV: 99% Gtot: 9%

GRIS




8271 UV: 99% Gtot: 7%

ANTRACITA




2796 UV: 99% Gtot: 6%

TWEED NEGRO



2085 UV: 99% Gtot: 6%

NEGRO



8275 UV: 99% Gtot: 5%

ORCHESTRA

ACRYLIC FABRICS

NAPLES LINEN



D307 UV: 95% G_{TOT}: 13% RAPPOR: 20 cm

NAPLES HEATHER



D305 UV: 90% G_{TOT}: 11% RAPPOR: 20 cm

NAPLES LIGHT GREY




D304 UV: 90% G_{TOT}: 11% RAPPOR: 20 cm

NAPLES STONE




D113 UV: 95% G_{TOT}: 7% RAPPOR: 20 cm

PENCIL BEIGE



D324 UV: 95% G_{TOT}: 14% RAPPOR: 30 cm

PENCIL YELLOW



D323 UV: 95% G_{TOT}: 13% RAPPOR: 30 cm

PENCIL GREY




D320 UV: 95% G_{TOT}: 14% RAPPOR: 30 cm

PENCIL DARK GREY




D319 UV: 100% G_{TOT}: 8% RAPPOR: 30 cm

WIDE CHINA YELLOW



D300 UV: 95% G_{TOT}: 13% RAPPOR: 60 cm

WIDE CHINA BEIGE



D301 UV: 95% G_{TOT}: 12% RAPPOR: 60 cm

WIDE CHINA GREEN




D299 UV: 95% G_{TOT}: 10% RAPPOR: 60 cm

URBAN


ACRYLIC FABRICS

CANDLELIGHT




0990 UV: 99% G_{TOT}: 9.6% RAPPOR: 6 cm

LANTERN



0991 UV: 99% G_{TOT}: 14.2% RAPPOR: 6 cm

CONCRETE



0993 UV: 99% G_{TOT}: 10.8% RAPPOR: 6 cm

TIMBER




0992 UV: 99% G_{TOT}: 9.6% RAPPOR: 6 cm

LANDSCAPE MINI


ACRYLIC FABRICS

CLAY




4627 UV: 99% Gtot: 11.3% RAPPORT: 2 cm

SAND




4620 UV: 99% Gtot: 11.4% RAPPORT: 2 cm

GRAVEL



4621 UV: 99% Gtot: 8.1% RAPPORT: 2 cm

LAVA



4623 UV: 99% Gtot: 8.3% RAPPORT: 2 cm

LANDSCAPE


ACRYLIC FABRICS

ROSOPSIDA



4657 UV: 99% Gtot: 14.96% RAPPORT: 24 cm

GOBI



4658 UV: 99% Gtot: 11.32% RAPPORT: 24 cm

BEACH



4662 UV: 99% Gtot: 16.37% RAPPORT: 24 cm

SAHARA DUST



4639 UV: 99% Gtot: 10.18% RAPPORT: 24 cm

CLIFFS



4643 UV: 99% Gtot: 6.78% RAPPORT: 24 cm

LADAKH



4655 UV: 99% Gtot: 5.91% RAPPORT: 24 cm

FJORD




4644 UV: 99% Gtot: 7.8% RAPPORT: 24 cm

NAMIB



4640 UV: 99% Gtot: 5.04% RAPPORT: 24 cm

VULCANO




4665 UV: 99% Gtot: 5% RAPPORT: 24 cm

CLASSICAL

ACRYLIC FABRICS

CLASSICAL GRIS



2103 UV: 97% G_{TOT}: 16% RAPPOR: 20 cm

CLASSICAL AMARILLO




2015 UV: 97% G_{TOT}: 15% RAPPOR: 20 cm

CLASSICAL MOSSY TWEED




9878 UV: 98% G_{TOT}: 15% RAPPOR: 20 cm

CLASSICAL STONE TWEED




0597 UV: 98% G_{TOT}: 12% RAPPOR: 20 cm

CLASSICAL BEIGE



2275 UV: 98% G_{TOT}: 14% RAPPOR: 20 cm

CLASSICAL MARRON BEIGE




2148 UV: 99% G_{TOT}: 9% RAPPOR: 20 cm

FANTASY


ACRYLIC FABRICS

MILANO




3868 UV: 95% G_{TOT}: 22% RAPPOR: 30 cm

CALGARY




6712 UV: 95% G_{TOT}: 16% RAPPOR: 30 cm

SUNRISE




0180 UV: 99% G_{TOT}: 14.73% RAPPOR: 30 cm

PALERMO




3605 UV: 90% G_{TOT}: 21% RAPPOR: 17 cm

ARGENTINA




2016 UV: 98% G_{TOT}: 15% RAPPOR: 30 cm

TARANTO




3672 UV: 95% G_{TOT}: 21% RAPPOR: 24 cm

CANBERRA




0452 UV: 98.75% G_{TOT}: 15.51% RAPPOR: 24 cm

DAKAR




2080 UV: 98% G_{TOT}: 15% RAPPOR: 40 cm

LISBONNE NATURE



8224 UV: 95% G_{TOT}: 13% RAPPORT: 30 cm

SALERNO




3861 UV: 90% G_{TOT}: 20% RAPPORT: 30 cm

MARTE



2121 UV: 99% G_{TOT}: 11% RAPPORT: 24 cm

BOLOGNA




3427 UV: 90% G_{TOT}: 22% RAPPORT: 20 cm

ALBERTA




5106 UV: 98% G_{TOT}: 15% RAPPORT: 30 cm

MANCHESTER




2823 UV: 98% G_{TOT}: 8% RAPPORT: 24 cm

JAMAICA



2701 UV: 98% G_{TOT}: 14% RAPPORT: 30 cm

BRISBANE




0186 UV: 98.1% G_{TOT}: 10.26% RAPPORT: 24 cm

SUNBURY



6106 UV: 98% G_{TOT}: 10% RAPPORT: 30 cm

HARDELOT NATURE




8935 UV: 95% G_{TOT}: 14% RAPPORT: 30 cm

EDMONTON




6711 UV: 98% G_{TOT}: 13% RAPPORT: 30 cm

OSLO FIRE




7351 UV: 95% G_{TOT}: 14% RAPPORT: 30 cm

SIENNE NATURE




D100 UV: 95% G_{TOT}: 14% RAPPORT: 30 cm

TEXAS




2238 UV: 98% G_{TOT}: 13% RAPPORT: 30 cm

WINTONE




0734 UV: 97.5% G_{TOT}: 12.39% RAPPORT: 24 cm

FOGGIA



3864 UV: 95% G_{TOT}: 18% RAPPORT: 30 cm

PERU




2201 UV: 98% G_{TOT}: 14% RAPPORT: 30 cm

ANDRIA




3881 UV: 95% G_{TOT}: 18% RAPPORT: 30 cm

BROKEN HILL




0497 UV: 95% G_{TOT}: 16% RAPPORT: 30 cm

NEW YORK




2174 UV: 98% G_{TOT}: 14% RAPPORT: 30 cm

METROPOLITAN



3608 UV: 99% G_{TOT}: 7% RAPPORT: 30 cm

GLADSTONE



0493 UV: 99% G_{TOT}: 7.78% RAPPORT: 24 cm

ANCONA




3746 UV: 90% G_{TOT}: 19% RAPPORT: 24 cm

SIENNE STONE




8931 UV: 95% G_{TOT}: 13% RAPPORT: 30 cm

PLUTON



2179 UV: 99% G_{TOT}: 10% RAPPORT: 24 cm

RAVENNA




3882 UV: 95% G_{TOT}: 19% RAPPORT: 30 cm

FIRENZE



3889 UV: 90% G_{TOT}: 20% RAPPORT: 30 cm

MELBOURNE



0054 UV: 99% G_{TOT}: 11.74% RAPPORT: 24 cm

ORLANDO



2191 UV: 98% G_{TOT}: 11% RAPPORT: 30 cm

CANADA



2061 UV: 99% G_{TOT}: 8% RAPPORT: 30 cm

PADOVA



3875 UV: 95% G_{TOT}: 17% RAPPORT: 30 cm

FABRIC RAPPORT

ACRYLIC FABRICS




24 cm | 24 cm | 24 cm | 24 cm | 24 cm | 24 cm | 24 cm | 24 cm | 24 cm | 24 cm

Multiply repeated pattern of fabric, expressed in cm and given in the chart.



SCREEN FABRICS



OPENNES FACTOR:

Relative area of the openings in the fabric. It is considered as independent of the colour. For fabric with the same weave, it should be measured using the darkest colour in the range.

SERGE 1 % (100) / SERGE 600

Collection of fabrics made from fiberglass covered with PVC. Fabrics made of this group have a distinctive diagonal „serge” weave, which guarantees them an unusual dimensional stability. High fire resistance and very good technical parameters of fabrics provide users with visual comfort in rooms, thus protecting against overheating the interior.

POLYSCREEN

Wide group of technical polyester fabrics coated with PVC, characterized by variety of weaving patterns and properties (PS Luminous, PS 550, PS 350). This allows architects to select the right solution, increasing visual attractiveness of the building and to emphasize its individual character. High technical parameters provide optical and thermal comfort inside the room. An additional feature of the fabric is the ease to keep it clean.

BLACK OUT

High-end blackout fabrics (Serge 600 BO Lunar, Polyscreen 314 BO) effectively block sunlight coming into the room. It is ideal solution for conference rooms, audio-visual, photographic studios, etc. High dimensional stability, high technical parameters and interesting colours are without a doubt advantages of fabrics in this group.

SUNWORKER


Smooth polyester fabric finished with PVC. Unique structure of the fabric effectively stops the sunlight, allowing for just optimal amount of visible light to transmit inside the room, providing high comfort to its users. The advantages of this fabric are: color fastness, high resistance to weather conditions and easy to maintain clean.

SOLTIS 92 / SOLTIS 99

Polyester technical fabric coated with PVC, manufactured with patented technology Precontraint Ferrari®. The unique technology gives fabric high stability and protects it against deformations even in large size blinds. High technical parameters guarantee optical and thermal comfort. The quality components used in production of this fabric ensures color fastness. Thanks to the smooth surface, the fabric is difficult to absorb dirt or get stained.

ACOUSTIC - VEROGLIM

Elegant fabric, made from the highest quality non-flammable polyester fibers Trevira® CS, intended for indoor use. Because of its weight, the fabric is ideally suited for cassette systems. An important advantage of this fabric is high coefficient of acoustics. Thanks to its structure, the fabric absorbs sound and mutes the room. Another advantage is metallic surface that reflects bright light and in this way regulates its intensity in the room.



SERGE 600

WHITE - WHITE



60002002

GREY - WHITE



60001002

PEARL - GREY




60007007

GREY - GREY




60001001

GREY - CHARCOAL



60001010

CHARCOAL - CHARCOAL



60010010

SERGE 600

PURE BLACK



60030030

CHARCOAL - BRONZE




60010011

SANDSTONE




60033033

GREY - SAND



60001003

LINEN - LINEN



60008008

LINEN - WITE




60008002

	composition	weight [g/m ²]	thickness [mm]	light fastness blue scale level EN ISO 105 B02 EN ISO 105 B04	openness factor [%]	EN 14501				application
						TS [%]	RS [%]	AS [%]	TV [%]	
White - White	42% glasfibre + 58% pvc	525	0.74	>7	5	21/21	65.9/66.3	13.2/12.7	21.2/21.2	interior / exterior SERGE 600
Grey - White						6.7/6.7	37.2/26.9	56.2/66.4	6.6/6.6	
Pearl - Grey						10.1/10.1	38.3/39.4	51.7/50.5	8.4/8.4	
Grey - Grey						3.5/3.5	15.1/15.1	81.3/81.4	3.6/3.6	
Grey - Charcoal						3.6/3.6	9.9/12.6	86.5/83.8	3.6/3.6	
Charcoal - Charcoal						3.6/3.6	5.0/4.8	91.4/91.6	3.6/3.6	
Tearing resistance (daN) UNE EN ISO 4674-1 method 2 - Warp: 8.5, Weft: 7.5 Breaking strength (daN/5cm) UNE EN ISO 1421 - Warp: 260, Weft: 225 Flame retardant - Certificate on request										



	composition	weight [g/m ²]	thickness [mm]	light fastness blue scale level EN ISO 105 B02 EN ISO 105 B04	openness factor [%]	EN 14501				application
						TS [%]	RS [%]	AS [%]	TV [%]	
Pure Black	42% glasfibre + 58% pvc	525	0.74	>7	5	5.9	3.7	90.4	5.9	interior / exterior SERGE 600
Charcoal - Bronze						6.1	6.5/6.0	87.4/87.9	6.1	
Sandstone						7.1	20.4/20.5	72.4/72.5	6.8	
Grey - Sand						4.7	26.5/21.5	68.8/73.8	4.5	
Linen - Linen						14.9	52.5/52.7	32.5/32.4	12.9	
Linen - Wite						15.5	58.2/56.4	26.4/28.1	13.7	
Tearing resistance (daN) UNE EN ISO 4674-1 method 2 - Warp: 8.5, Weft: 7.5 Breaking strength (daN/5cm) UNE EN ISO 1421 - Warp: 260, Weft: 225 Flame retardant - Certificate on request										



SERGE 1%

WHITE - WHITE



61002002

GREY - WHITE



61001002

PEARL - GREY




61007007

GREY - GREY




61001001

GREY - CHARCOAL




61001010

CHARCOAL - CHARCOAL




61010010

BRONZE - BRONZE



61011011

LINEN - LINEN



61008008

	composition	weight [g/m ²]	thickness [mm]	light fastness blue scale level EN ISO 105 B02 EN ISO 105 B04	openness factor [%]	EN 14501				application						
						TS [%]	RS [%]	AS [%]	TV [%]							
White - White	42% glasfibre + 58% pvc	638	0.78	>7	1	12.8	71.3	15.9	12.9	interior / exterior						
Grey - White						2.2	44.8/31.2	53/66.6	2							
Pearl - Grey						2.8	36.9	60.3	2.1							
Grey - Grey						2.4	17.4	80.2	2.2							
Grey - Charcoal						1.2	10.5/14	88.3/84.8	1.2							
Charcoal - Charcoal						1.1	5.9	93	1.1							
Bronze - Bronze						1.4	8.6	90	1.3							
Linen - Linen						5.9	54.2	39.9	3.7							
Tearing resistance (daN) UNE EN ISO 4674-1 method 2 - Warp: 5.9, Weft: 6.2 Breaking strength (daN/5cm) UNE EN ISO 1421 - Warp: 321, Weft: 277 Flame retardant - Certificate on request																


SERGE 1%



SERGE 600


BO LUNAR

WHITE - WHITE




680002002

WHITE - PERL GREY



680002007

PEARL GREY - PEARL GREY



680007007

WHITE - GREY



680001002

OYSTER SHELL




680033001

GREY - GREY



680001001

GREY - CHARCOAL



680001010

CHARCOAL - CHARCOAL



680010010


	composition	weight [g/m ²]	thickness [mm]	light fastness blue scale level EN ISO 105 B04	openness factor [%]	EN 14501				application						
						TS [%]	RS [%]	AS [%]	TV [%]							
White - White	33% GLASFIBRE 47% PVC 20% PVC LAMINATE	678	0.73	>7	0	0	68.8/33.7	31.2/66.3	0	interior / exterior						
White - Perl Grey						0	47.8/33.2	52.2/66.8	0							
Pearl Grey - Pearl Grey						0	35.5/34	64.5/66	0							
White - Grey						0	40.3/33.7	59.7/66.3	0							
Oyster Shell						0	18.2/33.4	81.8/66.6	0							
Grey - Grey						0	17.2/33.1	82.8/66.9	0							
Grey - Charcoal						0	11/33.7	89/66.3	0							
Charcoal - Charcoal						0	6.2/33.4	93.8/66.6	0							
Tearing resistance (daN) UNE EN ISO 4674-1 method 2 - Warp: 8.5, Weft: 9 Breaking strength (daN/5cm) UNE EN ISO 1421 - Warp: 224.2, Weft: 176.6 Flame retardant - Certificate on request																

SERGE 600 BO LUNAR




POLYSCREEN® 550

ASH (EBONY - GREY)




10550017

PEARL - GREY



10550013

WHITE - GREY




10550012

WHITE - PEARL




10550011

PEARL - SAND



10550023

PEARL - LINEN



10550021

WHITE - LINEN



10550019

WHITE



10550009

	composition	weight [g/m²]	thickness [mm]	light fastness blue scale level EN ISO 105 B02	light fastness grey scale level EN ISO 4892	openness factor [%]	internal method				application
							TS [%]	RS [%]	AS [%]	TV [%]	
Ash (Ebony - Grey)	85% PVC + 15% PES	610 ± 5%	0,78 ± 5%	8/8	5/5	5	6	7	87	6	interior / exterior
Pearl - Grey				8/8	5/5		11	29	60	9	
White - Grey				≥7/8	≥ 4/5		13	37	50	12	
White - Pearl				≥7/8	≥ 4/5		16	57	27	12	
Pearl - Sand				8/8	5/5		13	37	50	10	
Pearl - Linen				8/8	5/5		17	46	37	12	
White - Linen				≥7/8	≥ 4/5		20	63	17	16	
White				7/8	4/5		19	69	12	15	

Tearing resistance (daN) UNE EN ISO 13937-3:2001 - Warp: 6,6, Weft: 5,3
 Breaking strength (daN/5cm) UNE EN ISO 13934-1:1999 - Warp: 174, Weft: 133
 Stretch (%) UNE EN ISO 13934-1:1999 - Warp: 22%, Weft: 21%
 Flame retardant - certificate on request




0338

POLYSCREEN® 550


GOLD & SILVER

EBONY - GOLD




10550051

CRYSTAL - GOLD VISION




10550052

LINEN - GOLD



10550053

BRONZE - SILVER



10550041

GREY - SILVER



10550042

SILVER VISION



10550043

	composition	weight [g/m²]	thickness [mm]	light fastness blue scale level EN ISO 105 B02	light fastness grey scale level EN ISO 4892	openness factor [%]	internal method				application
							TS [%]	RS [%]	AS [%]	TV [%]	
Ebony - Gold	85% PVC + 15% PES	610 ± 5%	0.78	8/8	5/5	5	*	*	*	11	interior / exterior
Crystal - Gold Vision							18	17	65	22	
Linen - Gold							13	25	62	14	
Bronze - Silver							17	14	69	17	
Grey - Silver							16	17	67	17	
Silver Vision	21	23	56	22							

* On request
 Tearing resistance (daN) UNE EN ISO 13937-3:2001 - Warp 6,6, Weft 5,3
 Breaking strength (daN/5cm) UNE EN ISO 13934-1:1999 - Warp 174, Weft 133
 Stretch (%) UNE EN ISO 13934-1:1999 - Warp 22, Weft 21
 Flame retardant - certificate on request


POLYSCREEN® 550 GOLD & SILVER



0338


POLYSCREEN® 350

ASH (EBONY - GREY)




10550017

PEARL - GREY



10550013

WHITE - LINEN



10350019

WHITE



10350009

	composition	weight [g/m ²]	thickness [mm]	light fastness blue scale level EN ISO 105 B02	light fastness grey scale level EN ISO 4892	openness factor [%]	internal method				application
							TS [%]	RS [%]	AS [%]	TV [%]	
Ash (Ebony - Grey)	80% PVC + 20% PES	400 ± 5%	0.53 ± 5%	8/8	5/5	10	10	8	82	10	Interior
Pearl - Grey				8/8	5/5		16	26	58	14	
White - Linen				≥7/8	≥ 4/5		27	58	15	23	
White				7/8	4/5		25	64	11	22	

Tearing resistance (daN) UNE EN ISO 13937-3:2001 - Warp: 4.8, Weft: 5.2
 Breaking strength (daN/5cm) UNE EN ISO 13934-1:1999 - Warp: 145, Weft: 127
 Stretch (%) UNE EN ISO 13934-1:1999 - Warp: 21%, Weft: 23%
 Flame retardant - certificate on request

POLYSCREEN® 350



0338


POLYSCREEN® LUMINOUS

ARIZONA




10550061

SAHARA A



10550062

SAHARA B




10550062

KALAHARI




10550064

ATACAMA



10550065

MOJAVE



10550066

	composition	weight [g/m ²]	thickness [mm]	light fastness blue scale level EN ISO 105 B02	light fastness grey scale level EN ISO 4892	openness factor [%]	internal method				application	
							TS [%]	RS [%]	AS [%]	TV [%]		
Arizona	85% PVC + 15% PES	511 ± 5%	0.78	8/8	5/5	13	15	10	75	16	interior / exterior	
Sahara A		612 ± 5%	0.82				6	10	15	75		11
Sahara B		612 ± 5%	0.82				6	10	12	78		10
Kalahari		555 ± 5%	0.80				7	23	23	54		23
Atacama		594 ± 5%	0.77				10	20	14	66		22
Mojave		516 ± 5%	0.90				11	14	8	78		14

Tearing resistance (daN) - On request
 Breaking strength (daN/5cm) - On request
 Stretch (%) UNE EN ISO 13934-1:1999 - On request
 Flame retardant - On request

POLYSCREEN® LUMINOUS




0338

POLYSCREEN® 550


COUPAGE

COUPAGE 1




10550031

COUPAGE 2



10550032

COUPAGE 3



10550033

COUPAGE 4



10550034

	composition	weight [g/m ²]	thickness [mm]	light fastness blue scale level EN ISO 105 B02	light fastness grey scale level EN ISO 4892	openness factor [%]	internal method				application
							TS [%]	RS [%]	AS [%]	TV [%]	
Coupage 1	85% PVC + 15% PES coated with PVC	610 ± 5%	0.78	8/8	5/5	5	*	*	*	10	interior / exterior
Coupage 2							*	*	*	12	
Coupage 3							*	*	*	19	
Coupage 4							*	*	*	17	

* On request
 Tearing resistance (daN) UNE EN ISO 13937-3:2001 - Warp 6.6, Weft 5.3
 Breaking strength (daN/5cm) UNE EN ISO 13934-1:1999 - Warp 174, Weft 133
 Stretch (%) UNE EN ISO 13934-1:1999 - Warp 22, Weft 21
 Flame retardant - certificate on request

POLYSCREEN® 550 COUPAGE




0338

POLYSCREEN® 314


BLACK OUT

EBONY - GREY




10314B20

EBONY - LINEN




10314B08

LINEN - BRONZE




10314B06

WHITE




10314B02

LINEN - SAND



10314B04

EBONY - SAND



10314B10

	composition	weight [g/m ²]	thickness [mm]	light fastness blue scale level EN ISO 105 B02	light fastness grey scale level EN ISO 4892	openness factor [%]	EN 14501				application
							TS [%]	RS [%]	AS [%]	TV [%]	
Ebony - Grey	80% PVC + 20% PES coated with PVC	610 ± 5%	0.66 ± 5%	8 / 8	4/5	0	0	36	64	0	Interior
Ebony - Linen				8 / 8							
Linen - Bronze				8 / 8							
White				7 / 8							
Linen - Sand				8 / 8							
Ebony - Sand				8 / 8							

Tearing resistance (daN) UNE EN ISO 13937-3:2001 - Warp: 4.4, Weft: 2.5
 Breaking strength (daN/5cm) UNE EN ISO 13934-1:1999 - Warp: 147, Weft: 91
 Stretch (%) UNE EN ISO 13934-1:1999 - Warp: 26.7%, Weft: 17.6%
 Flame retardant - certificate on request

POLYSCREEN® 314 BLACK OUT



0338


SUNWORKER

WHITE



40SWK005

IRON



40SWK653

CHAMPAGNE



40SWK711

CHARCOAL



40SWK392

	composition	weight [g/m ²]	thickness [mm]	light fastness blue scale level EN ISO 105 B02	light fastness grey scale level EN ISO 105 B04	openness factor [%]	EN 14501				application
							TS [%]	RS [%]	AS [%]	TV [%]	
White	Polyester / PVC	300	0.42	7/8	4-5/5	6	23	66	11	21	interior / exterior
Iron						6	12	35	53	10	
Champagne						6	21	50	29	18	
Charcoalw						6	6	7	87	6	

Tearing strength (daN/5cm) DIN 53.363 - Warp: 43, Weft: 22
 Tensile strength (daN/5cm) NF EN ISO 13934-1 - Warp: 220, Weft: 150
 Flame retardant - certificate on request

SUNWORKER



SOLTIS® 92

CHARCOAL



50922047

CONCRETE



50922167

GLOSSY




50922065

SILVER




50922048

SILVER BLACK



50922045

SILVER - WHITE



50922051

SANDY BEIGE



50922135

WHITE



50922044

	composition	weight [g/m ²]	thickness [mm]	light fastness grey scale level EN ISO 105 B04	openness factor [%]	EN 14501				application
						TS [%]	RS [%]	AS [%]	TV [%]	
Charcoal	Polyester / PVC	420	0.45	5/5	4	5	8	87	5	interior / exterior
Concrete				5/5		6	19	75	5	
Glossy				4/5		10	46	44	7	
Silver				2/5		8	46	46	8	
Silver Black				5/5		4	35	61	4	
Silver - White				4/5, 3/5		12/12	49/70	39/18	11/11	
Sandy Beige				5/5		11	46	43	8	
White				2/5		19	68	13	17	

Tear strength (daN) DIN 53.363 - Warp: 45, Weft: 20
 Tensile strength (daN/5cm) EN ISO 1421 - Warp: 310, Weft: 210
 Flame retardant - certificate on request

SOLTIS® 92



SOLTIS® 99

WHITE



50992055

QUARTZ




509950285

SANDY BEIGE



509950286

SPUME



509950284

LIGHT GREY



50992058

ALU



50992059

ANTRACITE



50992068

	composition	weight [g/m ²]	thickness [mm]	light fastness grey scale level EN ISO 105 B04	openness factor [%]	EN 14501				application
						TS [%]	RS [%]	AS [%]	TV [%]	
White	Polyester / PVC	290	0.32	4/5, 4/5	3	14/14	47/63	39/23	13	interior
Quartz				4/5, 5/5		11/11	47/60	42/29	9	
Sandy Beige				4/5, 5/5		10/10	43/44	47/46	7	
Spume				4/5, 4/5		12/12	47/60	41/28	9	
Light Grey				4/5, 5/5		8/8	44/43	48/49	6	
Alu				4/5, 4/5		6	43	51	5	
Antracite				4/5, 5/5		3/3	33/8	64/89	3	

Tear strength (daN) DIN 53.363 - Warp: 11, Weft: 13
 Tensile strength (daN/5cm) EN ISO 1421 - Warp: 160, Weft: 170
 Flame retardant - certificate on request



SOLTIS® 99


VEROGLIM ACOUSTIC

GREY - SILVER




34022115

LIGHT GREY - SILVER



34022114

WHITE - SILVER



34022111

IVORY - SILVER



34022113

	composition	weight [g/m ²]	thickness [mm]	light fastness blue scale level EN ISO 105 B02	openness factor [%]	DIN EN 410				application
						TS [%]	RS [%]	AS [%]	TV [%]	
Grey - Silver	Trevira CS	220	0.43	5-6/8	1	5	50	45	2	interior
Light Grey - Silver						5	52	43	4	
White - Silver						7	52	41	7	
Ivory - Silver						6	49	45	6	

Breaking strength (daN/5cm) UNE EN ISO 13934-1:1999 - Warp: 95, Weft: 130
 Stretch (%) UNE EN ISO 13934-1:1999 - Warp: 35%, Weft: 23%
 Flame retardant - Certificate on request

VEROGLIM ACOUSTIC



$\alpha_w = 60\%$



PERGOLA SOLID FABRICS



PRECONTRAIT 602 OPAQUE


Technical specifications

	Values	Standards
Yarn	1100 dtex PES HT	Tersuisse
Weight	750 g/m ²	EN ISO 2286-2
Width	267 cm	-
Tensile strength (warp/weft)	230/220 daN/5cm	EN ISO 1421
Tear strenght (warp/weft)	20/20 daN	DIN 53.363
Elongation under load (warp/weft)	<1%/<1%	NF EN 15619
Adhesion	9/9 daN/5cm	EN ISO 2411
Finish	Varnish both sides	-
Flame retardancy	• M2/NFP 92-507 • B1/DIN4102-1 • M2/UNE23.727-90 • BS 7837 • 1530.3/AS NZS • Method 2/NFPA 701 • CSFM T19 •	
Cold resistance	-30°C	ISO 4675
Heat resistance	+70°C	

BLANC 602N OPAQUE 8503



BEIGE 602N OPAQUE 0020



PRECONTRAIT 702 OPAQUE

Technical specifications


	Values	Standards
Yarn	1100 dtex PES HT	Tersuisse
Weight	830 g/m ²	EN ISO 2286-2
Width	267 cm	
Tensile strength (warp/weft)	280/280 daN/5 cm	EN ISO 1421
Tear strength (warp/weft)	30/28 daN	DIN 53.363
Adhesion	10/10 daN/5 cm	EN ISO 2411
Finish	Acrylic varnish both sides Aluminium face / Back grey	
Flame retardancy	M2/NFP 92-507 • TEST 2/NFPA 701 • CSFM T19 • B1/DIN 4102-1 • BS 7837 • GROUP 1/AS/ NZS 3837 • 1530.3/AS/NZS • SITAC/SIS 650082 • Schwerbrennbar Q1-Tr1/ONORM A 3800-1 • CLASSE 2/UNI 9177-87 • M2/UNE 23.727-90 • VKF 5.2/SN 198898 • B-s2,do/EN 13501-1	
Cold resistance	-30°C	
Heat resistance	+70°C	

ALU GREY 702 OPAQUE 1285



COATING FINISH

SELT COLOURS



1. "fine structure - pearl mat"
2. "fine structure"
3. satin finish
4. mat finish
5. "artificial anode"

CONSTRUCTION COLOURS

Presented colour chart shows colours available within Selt collection for powder coated construction elements of Refleksols, venetian blinds and sunbreakers. Conditions of painting in colours included in the collection below and in other RAL colours – according to rules described in price lists of individual products. Because of technical and production reasons as well as due to different coating techniques, differences in colours between product components are possible. Presented pictures are for illustration purposes only. Colours may vary from actual ones. Any difference in shade does not constitute grounds for complaint.

SLATS COLOURS


Presented colour chart shows slat colours available within SELT collection. Conditions of painting in colours within Selt collection and other RAL colours – according to rules described in price list of venetian blinds. Because of technical and production reasons as well as due to different coating techniques, differences in colours between product components are possible. Presented pictures are for illustration purposes only. Colours may vary from actual ones. Any difference in shade does not constitute grounds for complaint. Customized perforation (layout and size of openings) and painting in colours outside of SELT collection are subject to individual arrangements in terms of price and conditions of implementation.



SLAT COLOURS


C50 / C80 / C80F / Z90

RAL 9016




C80

RAL 9010



C50 / C80 / C80F / Z90

RAL7035



C80 / Z90

RAL 7024



C80 / Z90

RAL 7016




C50 / C80 / C80F / Z90

RAL 7021



C80 / Z90

RAL 9005*



C80 / Z90

RAL 9006



C50 / C80 / C80F / Z90

RAL 9007




C50 / C80 / C80F / Z90

DB 703



C80 / Z90

RAL 1013




C80 / Z90

VSR 240*




C80 / Z90

VSR 780*



C80 / Z90

RAL 8014



C80 / Z90

RAL 3004**



C80 / Z90

RAL 5014**



C80 / Z90

RAL 1006**




C80 / Z90

Standard slat gloss 80% (satin)
* gloss 60% (semi-matt)
** colours available until stock lasts

SLAT COLOURS


C50 SLIM

0005 (~ RAL 1013)



C50 SLIM

0204 (~ RAL 9003)



C50 SLIM

0030




C50 SLIM

0038 (~ RAL 9006)




C50 SLIM

9007 (~ RAL 9007)



C50 SLIM

2901




C50 SLIM

0199 (~ RAL 7024)




C50 SLIM

0019 (~ RAL 9011)




C50 SLIM

0204 PF (~ RAL 9003)



C50 SLIM

0038 PF (~ RAL 9006)




C50 SLIM


CONSTRUCTION

COLOURS


RAL 9016 MAT




RAL 9010 MAT



RAL 9001 MAT



RAL 1013 MAT



RAL 1015 MAT



RAL 1006 MAT



RAL 7035 MAT



RAL 7001 MAT



RAL 5014 MAT



RAL 7037 MAT



RAL 7012 MAT



RAL 7015MAT



RAL 7024 MAT



RAL 7016 MAT




RAL 7021 MAT



CONSTRUCTION

COLOURS

RAL 9005 MAT



RAL 9006 MAT



RAL 9007 MAT



DB 703 MAT




FSM 71319 MAT



RAL 8014 MAT




RAL 8016 MAT



RAL 3004 MAT



VSR 240 SATIN



VRS 780 MAT



SELT COMPANY

All specifications, design and color of products are up to date at time of forwarding this catalogue to print. The manufacturer reserves the right to make changes without prior notice. Due to the printing process any color reproductions are for illustration purposes only, their deviation from the actual color cannot constitute grounds for complaint. Folder reproduction in whole or in part is forbidden without the written permission of SELT.

selt.com